



UK Sampling Gauges Ltd

Building 1, Roman Bank, Bourne, Lincolnshire, PE10 9LQ, UK

Tel: +44 (0)1778 392818 Fax: +44 (0)1778 421169

E-mail: sales@samplinggauges.com

Web site: www.samplinggauges.com



Handy Lift & Lower Cable

Applications

There are situations in which an operator needs to take a sample of liquid from a relatively shallow tank or container. This might be in a road tanker or fuel barge, for example. In such situations, a "fully-fledged" winder would be seen as unduly expensive and complex.

At the same time, attempting to support the sampler by a length of simple cord is not to be recommended, because:

- a) the cord might fray and break, causing loss of the sampler,
- b) the cord might absorb some of the liquid, resulting in contamination of the sample, and
- c) the cord may not provide adequate protection against the build-up of static electricity.



Our "Handy" Lift & Lower Cable is the ideal solution. It is made from the same 2 mm Ø stainless steel multi-strand cable that we use in our winders. This means that it can't fray or break in operation. No liquid is absorbed into the cable, so there is no contamination. The cable incorporates our own design of hook. This means maximum security for your samplers. And the winder is supplied with an earthing connection for maximum safety in sampling flammable liquids.

Specifications

Cable Length and Diameter	5m x 2mm
---------------------------	----------



Please contact us, or scan the QR code, if you require further information about these or other equipment offered by **UK Sampling Gauges Ltd**, or if you require equipment to be adapted or modified.