



UK Sampling Gauges Ltd

Building 1, Roman Bank, Bourne, Lincolnshire, PE10 9LQ, UK

Tel: +44 (0)1778 392818 Fax: +44 (0)1778 421169

E-mail: sales@samplinggauges.com

Web site: www.samplinggauges.com



Winder MK 2/2, with Depth Counter for Restricted Sampling

Applications

The MK 2/2 Winder meets the need for sampling under restricted conditions, and where sample sizes of up to 1-litre are required. It will accept samplers with an overall diameter of up to 45 mm.

It is designed to fit directly onto a 2-inch (50 mm) vapour control valve, with coupling supplied to suit. The winder can also be supplied with an adaptor to suit alternate valve types. This feature is useful when sampling several different vessels with differing valve types.

The sampler itself is enclosed within the winder's main tube, so vapour and/or gas present above the cargo can escape only through the small gap in the top valve, through which the cable passes.

The winder incorporates our winding handle, which locks the reel automatically as soon as the operator releases the winding knob.

This version includes a gear-driven depth counter, to give the operator a clear indication of the depth of the sampler at all times throughout the sampling process.

A complete range of sampling equipment, capable of passing through 2-inch vapour control valves, is available for use with this winder, offering you representative samples under safe conditions and saving time and money.



MK 2/2 Winder
with UTI Type 2-inch coupling
(alternative coupling available to suit)

Specifications

Sampling / Gauging depth	Up to 30m
Weight of winder	4.5kg
Sample volume	Up to 1000ml
Material	316 Stainless Steel

Please contact us if you require further information about this or other equipment offered by **UK Sampling Gauges Ltd**, or if you require equipment to be adapted or modified.